

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

NowoSeal SB

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Impregnation

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

NOWOCOAT INDUSTRIAL A/S

Stålvvej 3

6000 Kolding

tlf: +45 7550 1111

mail@nowocoat.dk

Contact person

Annette Søgaard

E-mail

mail@nowocoat.dk

SDS date

28-03-18

SDS Version

4.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Asp. Tox. 1; H304

EUH066

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

May be fatal if swallowed and enters airways. (H304)

Repeated exposure may cause skin dryness or cracking. (EUH066)

According to EC-Regulation 2015/830

Safety statement(s)

General	-
Prevention	-
Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. (P301+P310+P331).
Storage	-
Disposal	Dispose of contents/container to an approved waste disposal plant. (P501).

▼ Identity of the substances primarily responsible for the major health hazards

Alkanes, C11-15-iso-, C11-12 Isoalkanes, C11-13 Isoalkanes

2.3. Other hazards

This product contains substances that can cause chemical pneumonia if inhaled. The symptoms of chemical pneumonia may appear after several hours.

This product contains an organic solvent. Repeated or prolonged exposure to organic solvents may result in adverse effects to the nervous system and internal organs such as liver and kidneys.

Additional labelling

-

Additional warnings

Not applicable.

▼ VOC

VOC-MAX: 15 g/l, MAXIMUM VOC CONTENT (A/c (SB)): 430 g/l.

SECTION 3: Composition/information on ingredients

▼ 3.1/3.2. Substances/Mixtures

NAME:	Alkanes, C11-15-iso-
IDENTIFICATION NOS.:	CAS-no: 90622-58-5 EC-no: 292-460-6 REACH-no: 01-2119456810-40
CONTENT:	80-95%
CLP CLASSIFICATION:	Asp. Tox. 1 H304, EUH066

NAME:	C11-13 Isoalkanes
IDENTIFICATION NOS.:	EC-no: 920-901-0 REACH-no: 01-2119456810-40
CONTENT:	2.5 - <5%
CLP CLASSIFICATION:	Asp. Tox. 1 H304

NAME:	C11-12 Isoalkanes
IDENTIFICATION NOS.:	EC-no: 918-167-1 REACH-no: 01-2119472146-39
CONTENT:	2.5 - <5%
CLP CLASSIFICATION:	Flam. Liq. 3, Asp. Tox. 1 H226, H304

NAME:	(2-Methoxymethylethoxy)propanol
IDENTIFICATION NOS.:	CAS-no: 34590-94-8 EC-no: 252-104-2
CONTENT:	1 - <2.5%
CLP CLASSIFICATION:	NA
NOTE:	SL

(* See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.
S = Organic solvent L = European occupational exposure limit.

Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service (dial 111, 24 h service).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 15 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Do not induce vomiting! If vomiting occurs, keep head facing down to prevent vomit entering the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should be kept under medical attention for a minimum of 48 hours.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if inhaled. The symptoms of chemical pneumonia may appear after several hours.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get immediate medical advice/attention.

Information to medic

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

No specific requirements.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances. Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

(2-Methoxymethylethoxy)propanol
Long-term exposure limit (8-hour TWA reference period): 50 ppm | 308 mg/m³
Short-term exposure limit (15-minute reference period): - ppm | - mg/m³
Comments: Sk (Sk = Can be absorbed through skin.)

▼ DNEL / PNEC

DNEL ((2-Methoxymethylethoxy)propanol): 283 mg/kg bw/day
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - Workers
DNEL ((2-Methoxymethylethoxy)propanol): 308 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - Workers
DNEL ((2-Methoxymethylethoxy)propanol): 121 mg/kg bw/day
Exposure: Dermal
Duration of Exposure: Long term – Systemic effects - General population
DNEL ((2-Methoxymethylethoxy)propanol): 37,2 mg/m³
Exposure: Inhalation
Duration of Exposure: Long term – Systemic effects - General population
DNEL ((2-Methoxymethylethoxy)propanol): 330 µg/kg bw/day
Exposure: Oral
Duration of Exposure: Long term – Systemic effects - General population

PNEC ((2-Methoxymethylethoxy)propanol): 19 - 19.2 mg/L
Exposure: Freshwater
Duration of Exposure: Single
PNEC ((2-Methoxymethylethoxy)propanol): 1.9 - 1.92 mg/L
Exposure: Marine water
Duration of Exposure: Single
PNEC ((2-Methoxymethylethoxy)propanol): 190 - 192 mg/L
Exposure: Intermittent release
Duration of Exposure: Continuous
PNEC ((2-Methoxymethylethoxy)propanol): 2.2 - 2.74 mg/kg soil dw
Exposure: Soil
Duration of Exposure: Single

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.


Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep containment materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

Recommended: A. Class 2 (medium capacity). Brown.

▼ Skin protection

Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.

Hand protection

Recommended: Polyvinyl alcohol (PVA). See the manufacturer's instructions.

▼ Eye protection

Wear face shield alternatively safety glasses with side shields.

SECTION 9: Physical and chemical properties

▼ 9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	No data available.
Odour	No data available.
Odour threshold (ppm)	No data available.
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm ³)	0,7-0,9

Phase changes

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

Data on fire and explosion hazards

Flash point (°C)	>61
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

Solubility

Solubility in water	Insoluble
n-octanol/water coefficient	No data available.

9.2. Other information

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: (2-Methoxymethylethoxy)propanol
Species: Rat
Test: LD50
Route of exposure: Oral
Result: 5000 - 5230 mg/kg bw

Substance: (2-Methoxymethylethoxy)propanol
Species: Rabbit
Test: LD50
Route of exposure: Dermal
Result: 19020 mg/kg bw

Skin corrosion/irritation

No data available.

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term effects

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: Ecological information

12.1. Toxicity

Substance: (2-Methoxymethylethoxy)propanol
Species: Daphnia
Test: LC50
Duration: 48 h
Result: 1 - 1.919 g/L

Substance: (2-Methoxymethylethoxy)propanol
Species: Fish
Test: LC50
Duration: 96 h
Result: 1 g/L

Substance: (2-Methoxymethylethoxy)propanol
Species: Algae
Test: EC50
Duration: 72 h
Result: 969 mg/L

▼ 12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
(2-Methoxymethylethoxy)propano...	Yes	Manometric Respirometry Test	96 %

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
(2-Methoxymethylethoxy)propano...	No	0,0043	No data available

According to EC-Regulation 2015/830

12.4. Mobility in soil

(2-Methoxymethylethoxy)propano...: Log Koc= 0,08180517, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

Nothing special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Waste

EWC code

08 01 11*

waste paint and varnish containing organic solvents or other dangerous substances

Specific labelling

-

Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

14.1. UN number -
14.2. UN proper shipping name -
14.3. Transport hazard class(es) -
14.4. Packing group -
Notes -
Tunnel restriction code -

IMDG

UN-no. -
Proper Shipping Name -
Class -
PG* -
EmS -
MP** -
Hazardous constituent -

IATA/ICAO

UN-no. -
Proper Shipping Name -
Class -
PG* -

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

-

Additional information

VOC-MAX: 15 g/l, MAXIMUM VOC CONTENT (A/c (SB)): 430 g/l.

Seveso

-

Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No.

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

EUH066 - Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

-

Additional label elements

Not applicable

Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

Annette

Date of last essential change (First cipher in SDS version)

28-03-18

Date of last minor change (Last cipher in SDS version)

28-03-18